



Model	UPS-500D	UPS-1000D	UPS-1200D	UPS-3000D	UPS-6000D	UPS-10000D
Power	500VA /300W	1000VA /600W	1200VA /750W	3000VA /1800W	6000VA /4500W	10000VA /6000
Technology	Line Interactive					
Input	Input Voltage Range	165-275Vac/90Vac-140Vac±3%				
	Nominal Input Voltage	220/230/240/110/120Vac				
	Input Frequency	50/60Hz				
Output	Nominal Output Voltage	220/230/240VAC				
	Output Voltage Range (Normal Mode)	220/230/240+10%-15%				
	Output Voltage Range (Battery Mode)	220/230/240±10%				
	Output Frequency (Normal Mode)	Synchronized(Sine Wave)				
	Output Frequency (Battery Mode)	50/60Hz				
	Wave Form	Step Wave				
	Power Factor	0.65				
Efficiency	> 90%					
Transfer Time	< 10ms					

Batteries & Runtime	Battery Type	Maintenance-free Sealed Lead-Acid Battery, Leak proof
	Included Battery Modules	Model dependent
	Runtime	Full Load 4 Minutes
		Half Load 12 Minutes
Charge Time	< 12 Hours (90%)	

LCD Status Display		Output Voltage, Normal, Fault, Battery, Overload, Battery Level
Audible Alarm	Buzzer	AC Unusual/Battery Low Voltage/Overload/Short Circuit/PCB Failed, Beep for 240 Seconds
Interface Port(s)	Interface	RS-232/USB
	Control Software	UPSlion2000
Cold-start Capability		Yes
Protection	Surge Protection and Filtering	High Voltage, Low Voltage, Surge, Spike
	Overload Protection	120%-150%
	Battery Low Voltage Protection	Model dependent
	Output Short Circuit Protection	Output auto cut off, Buzzer beeping
	EMI Filter	Yes
	Tel/Fax/Modem Jack	Yes
Operating Conditions	Operating Temperature	0-40°C
	Storage Temperature	-15-45°C
	Operating Relative Humidity	10%RH-95%RH,Non-condensing

Agent details:

Economic Co. for electrical commerce and import

Tel/Fax: 0020-2590-7882

Website: www.economic-ec.com

Email: economic@economic-ec.com